

Eastto CALIBRATION FLUIDS 2, 5

GRADE: VG2,5

INTRODUCTION:

Eastto CALIBRATING FLUIDS 2, 5 are simulated fuels with properties similar to diesel fuel. These specially developed fluids are not only safer to use, but are formulated to meet tighter, more demanding specifications required in the manufacturing processes used by the fuel system component manufacturers when building fuel pumps, fuel injectors and fuel, air and oil filters. These fluids contain a range of special additives to enhance corrosion resistance, oxidation stability and anti-wear. EASTO CALIBRATING FLUIDS 2, 5 are more suitable than commercially refined fuels for use in manufacturing processes due to the precisely controlled viscosity, density, higher & safer flash points and lower aromatic hydrocarbon content.

APPLICATION:

EASTO CALIBRATING FLUIDS 2, 5 are recommended for the calibration of fuel pumps, fuel injectors and fuel, air and oil filters.

TYPICAL PROPERTIES:

CHARACTERISTICS	CALIBRATION FLUIDS 2	CALIBRATION FLUIDS 5
Kinematic Viscosity at 40°C., cSt,	1.98 -2.42	4.14 - 5.06
Flash Point, PMCC, °C, Min.	75	130
Pour Point, °C. Max.	(-) 6	(-) 6

PACKING: 210 Litres Drum, 50 Litres, 20 Litres, 5 Litres, 1 Litre



Eastern Petroleum Private Limited

Regd. Off.:

Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Calibration Fluids 2, 5