

PRODUCT DATA SHEET

PRODUCT: EASTTO 2T OIL

GRADE: TWO STROKE ENGINE OIL

INTRODUCTION: EASTTO 2T OIL is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of two stroke engines manufactured by all leading auto makers. It is blended from selected base stocks and special additives to minimise spark plug fouling and pre - ignition, prevent rusting, minimise deposit formation and provide protection against seizure, scuffing and wear. It is specifically formulated to give additional advantage of lower consumption of fuel. It contains a diluent for easy mixing with gasoline and is dyed green for easy identification.

APPLICATION: EASTTO 2T OIL is recommended for lubrication of Mopeds, Scooters, Motorcycles and Auto rickshaws, operating on two stroke engines. The recommended dosage is 20 ml of oil per litre of petrol.



Motorcycles and mopeds operating on two stroke engines



Auto rickshaws with two stroke engines

PERFORMANCE LEVEL: EASTTO 2T OIL meets the performance level of JASO FC specifications.

TYPICAL PROPERTIES

CHARACTERISTICS	TEST METHODS	EASTTO 2T OIL
Kinematic Viscosity at 40°C, cst	ASTM D 445	55
Flash Point, COC, °C	ASTM D 92	200
Sulphated Ash, % by Weight, Max.	ASTM D 874	0.25
Pour Point, °C	ASTM D 97	-12

PACKING: 100 ml Pouch, 500 ml bottle, 1 liter, 5 liters, 20 liters, 50 liters, 210 liters

Date of issue: 04.09.2014

Date of revision: 05.03.2019

PDS: 01.17.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

