

Eastto Circulating Oils

GRADE: VG 22, 32, 46, 68, 100, 150, 220, 320 and 460

INTRODUCTION:

Eastto Circulating Oils are specially developed for circulating and hydraulic transmission system. They are manufactured from highly refined base stocks with high viscosity index and are fortified with anti-oxidant, anti-corrosion, anti-wear, anti-rust and anti-foam additives.

APPLICATION:

EASTTO CIRCULATING OILS are suggested for moderate hydraulic systems and wide variety of circulating systems of industrial equipments.

PERFORMANCE LEVEL: IS: 3098:1983 [Reaffirmed FEBRUARY, 2004]

TYPICAL PROPERTIES

EASTTO CIRCULATING OILS									
	22	32	46	68	100	150	220	320	460
KV at 40°C	21-23	30-34	44-48	66-70	95-105	145-155	210-230	310-330	440-480
VI, Min.	98	95	95	95	95	95	95	95	95
Flash Point, COC, °C, Min.	160	190	210	210	210	220	220	230	230
Pour Point, °C, Max.	-9	-9	-9	-9	-6	-6	-6	-6	-6

PACKING: 210 Litres Drum



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Circulating Oils