

Eastto Glass Mould Oils

INTRODUCTION: EASTTO GLASS MOULD OILS 10, 15 & 22 are non-graphite type glass mould oils used for de-moulding in glass moulding industry. The oils are blended from highly refined base oils and specially selected additives. They provide instant de-moulding performance with good surface finish to the moulded products without any colouration of the glasses. They are non-toxic and do not cause fuming during use with unique property of inherent lubricity, low evaporation loss and moderately high fire points.

APPLICATION: EASTTO GLASS MOULD OILS 10, 15 & 22 can be applied by spraying or with swab and are recommended for different glassware and glass bottles etc.

PERFORMANCE LEVEL: EASTTO GLASS MOULD OILS 10, 15 & 22 meet IS: 12927 – 1990 (RA 2004)(Non-graphite Type).

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO GLASS MOULD OILS		
	VG 10	VG 15	VG 22
Kinetic Viscosity at 40oC, cSt,	9.0 to 11.0	14.0 to 16.0	20.0 to 24.0
Colour, ASTM, Max.	2.0	3.0	4.0
Flash Point, COC, °C, Min.	110	130	150
Pour Point, °C. Max.	3	3	3

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto
Glass Mould Oils



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

