

PRODUCT DATA SHEET

PRODUCT: EASTTO LOW VISC PX- 3

GRADE: EASTTO BASE OIL PX- 3

INTRODUCTION: Eastto Base Oil PX-3 is used along with resins dyes, etc. This is a transparent light coloured products having varied solvency. This is highly refined paraffinic hydrocarbon fractions having excellent oxidation and chemical stability with high flash points.

APPLICATION: Eastto Base Oils PX-3 can be used as diluents in many industrial applications, such as Metal Working Fluids, Water Treatment Chemicals, Silicone, Sealants, Cosmetic, Polishes, Varnishes and as a lubricant in Rubber minute machine parts.



Base Oils PX-3 can be used as diluents in such as Cosmetics, polishes and Metal working fluid

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO LOW VISCOSITY BASE OIL PX-3
Appearance	Clear Liquid
Colour, ASTM Max	Colourless
Density @ 29.5 Deg C gm/ml.	0.811
Kinematic Viscosity @ 40 Deg C, cSt.	3.53
FBP Deg C	322
IBP Deg C	258
Flash Point, COC Deg C	126
Pour Point Deg C	-18
Aniline Point Deg C	91
Water Content	16 ppm
Aromatic Content	50 ppm
Refractive Index at 20 Deg C	1.45

PACKING: 210 Litres Drums

Date of issue: 24.12.2014

Date of Revision: 30.07.2016

EASTERN PETROLEUM PVT. LTD. These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of **EASTERN PETROLEUM PVT. LTD.**

