

Eastto Marine HYD Oil

ISO VG 15, 32, 46, 68 & 100.

INTRODUCTION:

Eastto MARINE HYD oils are blended from Naphthenic Base Stocks containing Antioxidant, Anti-wear, Anticorrosion and antifoam additives.

APPLICATION: Recommended for use in Marine Hydraulic systems of steering Gears, Hatch Covers,

TYPICAL PROPERTIES:

Characteristics	Eastto Marine HYD Oil				
	15	32	46	68	100
Kinematic Viscosity at 100°C, cst	15	32	46	68	100
Viscosity Index	95	95	95	95	95
Flash Point °C, Min.	160	190	210	210	220
Pour Point, °C	-12	-15	-15	-15	-15

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Marine HYD Oil