

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO MAX 110 (PARAFFINIC RICH LOW AROMATIC SOLVENT)	
INTRODUCTION:	EASTTO MAX 110 is chemically processed specially formulated superior solvent, free from aromatics and unsaturated hydrocarbons. It is odorless, clear and colourless liquid.	
APPLICATION:	It is widely used in manufacture of Electrical contact cleaner spray, Metal degreasing products, Specialty lubricants, Agrochemicals, Paints, Printing inks, Rust preventives, Aerosols, Ultra sonic cleaning agent, Thinner, Lube oil additives, Pesticides, Insecticide, Fuel additive, Drilling fluid, Mosquito repellents and a solvent for industrial application.	







Electrical Contact Cleaner Spray, Rust Loosener, Metal Degreasing Products, Agrochemicals

TYPICAL PROPERTIES:

SR. NO.	CHARACTERISTICS	EASTTO MAX 110
1.	Appearance	Bright & Clear Liquid
2.	Odor	Odorless
3.	Specific Gravity @ 30 °C	0.78
4.	Acidity	Nil
5.	Flash Point °C	109
6.	Kinematic Viscosity @ 40 °C, cst	1.4
7.	Aromatics	Less than 1%
8.	Boiling Range – IBP °C	240
9.	FBP °C	277

PACKING: 210 Liters M. S. Drums, 26 Liters, 20 Liters & Tanker Load.

Date of Issue: 20.12.2014, Rev Date: 02 Mar 2019

Date of Revision: 06.03.2017

PDS No. 11.10.04

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

