

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2015 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO MAX 80 [PARAFFANIC RICH LOW ARROMATIC SOLVENT]	
INTRODUCTION:	This is chemically processed specially formulated solvent, free from Aromatics and unsaturated hydrocarbons, almost odorless clear and colorless liquid.	
APPLICATION:	This product is widely used in manufacture of Polish, metal degreasing products, specialty lubricants, agrochemicals, paint industries, ink industries, rust preventives, lube oil additives, pesticides, insecticide, specialty chemicals, fly sprays, fuel additive and a solvent for Industrial application.	







Electrical Contact Cleaner Spray, Rust Loosener, Metal Degreasing Products, Agrochemicals

TYPICAL PROPERTIES:

SR. NO.	PROPERTIES	RESULT - TYPICAL
1	Appearance	Bright & Clear Liquid
2	Colour (Lovibond)	Less than 0.5
3	Odour	Odorless, Non - Offensive
4	Specific Gravity @ 29.5°C	0.74 - 0.800
5	Solubility in Water	Insoluble
6	Acidity	Nil
7	Flash point (PMCC) ⁰ C	96
8	Kinematic Viscosity at 40 ⁰ C, cSt	1.4
9	Aromatics	Less than 1%
10	Sulphur, ppm	Less than 50 ppm
11	BOILING RANGE - IBP	205
	BOILING RANGE - FBP	266
12	Recovery, %	98%

PACKING: 210 Liters M.S. Drums/ TANKER LOAD

Date of issue: 30.04.2016, Rev Date: 02 Mar 2019

PDS No. 18.10.02

EASTERN PETROLEUM PVT. LTD. These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

