

Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India. Tel.: +91 - 22 - 4232 4121, 2529 9990, Email: office@easternpetroleum.in, Web:www.easternpetroleum.in CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

| PRODUCT: | EASTTO MAX SERIES (PARAFFINIC RICH LOW AROMATIC SOLVENTS) |
|---------------|---|
| INTRODUCTION: | EASTTO MAX SERIES are chemically processed specially formulated solvents, free from aromatics and unsaturated hydrocarbons. These are odourless, clear and colourless liquid. |
| APPLICATION: | These products are widely used in manufacture of Polish, Metal degreasing products, Specialty lubricants, Agrochemicals, Paints, Printing inks, Rust preventives, Aerosols, Ultra sonic cleaning agent, Thinner, Lube oil additives, Pesticides, Insecticide, Specialty chemicals, Fuel additive, Drilling fluid, Mosquito repellents and a solvent for industrial application. |



Metal Degreasing Products, Agrochemicals, Rust preventive products etc.

TYPICAL PROPERTIES:

| SR. NO. | CHARACTERISTICS | EASTTO MAX- A | EASTTO MAX 65 | EASTTO MAX 80 | EASTTO MAX 110 |
|---------|-------------------------------------|-----------------------|-----------------------|-----------------------|-----------------------|
| 1. | Appearance | Bright & Clear Liquid |
| 2. | Odour | Odourless | Odourless | Odourless | Odourless |
| 3. | Specific Gravity @ 30 °C | 0.77 | 0.78 | 0.77 | 0.78 |
| 4. | Acidity | Nil | Nil | Nil | Nil |
| 5. | Flash Point ^o C | 65 | 70 | 96 | 109 |
| 6. | Kinematic Viscosity @ 40 °C, cst | 1.7 | 1.2 | 1.5 | 1.4 |
| 7. | Aromatics | Less than 1% | Less than 1% | Less than 1% | Less than 1% |
| 8. | Boiling Range – IBP °C | 180 | 171 | 205 | 240 |
| 9. | FBP ⁰C | 240 | 222 | 266 | 277 |

PACKING: 20 Litres M. S. Drums / Tanker Load.

Date of Issue: 20.12.2014

Date of Revision: 11.08.2016

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

