

Eastto Polypropylene Wax

DESCRIPTION : Waxes are low melting inert products usually snow white in colour. These could be of natural origin e.g. bees wax or synthetics e.g. polypropylene wax etc. Then there are paraffin waxes- a bye-product of base oil manufactured from petroleum crude or microcrystalline waxes which are removed from base oils for lowering their pour point.

APPLICATION : Used as additives to improve the melting point of formulations. Have excellent water proofing properties, provide film strength capability, lubricity and wear protection. Used with profit in anti-sound special purpose greases together with MoS₂ where water washing resistance is desired. It can also be useful for paints and pigments.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTOWAX-10	EASTTOWAX-20
COLOUR	WHITE	WHITE
ODOUR	NONE	NONE
BULK DENSITY G/L	0.20 - 0.30	0.20 - 0.30
MELTING POINT 0C	112- 125	120 - 135
WATER CONTENT % MAX.	0.5	0.5

PACKING: 210 Litres Drums



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company



Eastto Polypropylene Wax



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

