

PRODUCT DATA SHEET

PRODUCT: EASTTO SHOCK ABSORBER OIL 12, 18

INTRODUCTION: EASTTO SHOCK ABSORBER OIL 12, 18 are blended from high viscosity index oils and specially selected additives to provide excellent anti-wear, anti-rust and anti-oxidation properties. EASTTO SHOCK ABSORBER OIL 12, 18 have very good chemical stability, excellent seal compatibility and very low pour point characteristics.

APPLICATION: EASTTOSHOCK ABSORBER OIL 12, 18 are recommended for use in shock absorbers.



PERFORMANCE LEVEL: Proprietary product

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO SHOCK ABSORBER OIL 12	EASTTO SHOCK ABSORBER OIL 18
Kinematic Viscosity at 40°C, cst	12	18
Viscosity Index, Min.	45	45
Flash Point, COC, °C, Min.	145	160
Pour Point, °C	-39	-36

PACKING: 210 Litres Drums.

Date of issue: 09.09.2014

Date of revision: 26.08.2016

PDS No. 01.45.01 – 01.46.02

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

