

Product Data Sheet

PRODUCT: EASTTO ULTRA TC 10W, 30, 40, 50

GRADE: SAE 10W, 30, 40, 50

INTRODUCTION: EASTTO ULTRA TC 10W, 30, 40, 50 are heavy duty diesel engine oils blended from highly refined base stocks and selected additives, and they have high level of detergency, excellent thermal and oxidation stability with superior performance under severe conditions.

APPLICATION: EASTTO ULTRA TC 10W, 30, 40, 50 are recommended for turbocharged diesel engines of heavy duty commercial vehicles, earth moving equipments, multi utility vehicles etc.



Ultra TC 10W, 30, 40, 50 are recommended for turbocharged diesel engines of heavy duty commercial vehicles.

PERFORMANCE LEVEL: Meets the performance level of API CD, IS: 13656-2014, EDL-2

TYPICAL PROPERTIES

| CHARACTERISTICS | EASTTO ULTRA TC 10W | EASTTO ULTRA TC 30 | EASTTO ULTRA TC 40 | EASTTO ULTRA TC 50 |
|-------------------------------------|---------------------|--------------------|--------------------|--------------------|
| Kinematic Viscosity at 100°C., cSt, | 5 Min. | 10.0 – 12.0 | 13.0 – 15.0 | 18.0 – 20.0 |
| Viscosity Index, Min. | 100 | 90 | 90 | 90 |
| Flash Point, COC, °C Min. | 220 | 220 | 220 | 220 |
| TBN, mg KOH / gm | 9.0 – 11.0 | 9.0 – 11.0 | 9.0 – 11.0 | 9.0 – 11.0 |

PACKING: 210, 20 Litres Drums.

Date of issue: 09.09.2014

PDS No. 01.02.01 – 01.02.04

PDS No. 01.31.02 / 01.31.04 These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of EASTERN PETROLEUM PVT. LTD.

