

## PRODUCT DATA SHEET

<b>BRAND:</b>	<b>EASTTO SPECIAL STEAM CYLINDER OIL</b>
<b>GRADES:</b>	<b>800</b>
<b>INTRODUCTION:</b>	These are highly refined steam cylinder oils having excellent chemical and thermal stability and load carrying ability. This oil reduces steam consumption due to good sealing characteristics and minimizes frictional losses.
<b>APPLICATION:</b>	Recommended as cylinder lubricants for steam engines handling superheated steam. It is recommended where Heavy loads, Slow speeds or High temperatures demands high viscosity lubricants in bearings and enclosed gear sets. It is suitable for worm gear boxes.



Recommended as lubricants for steam engines and cylinder.

<b>PERFORMANCE LEVEL:</b>	<b>Proprietary product</b>
---------------------------	----------------------------

### TYPICAL PROPERTIES:

TYPICAL PROPERTIES	EASTTO SPECIAL STEAM CYLINDER OIL 800
Kinematic Viscosity @ 40°C, cst	800
Viscosity Index	85
Flash Point (COC) °C	280
Pour Point °C	-3

**PACKING:** 210 Litres Drum

**Date of Issue** : 13.09.2014

**Date of revision:** 08.08.2016

**PDS No.** 20600 - 20602

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.



## PRODUCT DATA SHEET

**BRAND:** EASTTO STEAM CYLINDER OILS

**GRADES:** 680, 1000, 1500

**INTRODUCTION:** These are highly refined steam cylinder oils having excellent chemical and thermal stability and load carrying ability. This oil reduces steam consumption due to good sealing characteristics and minimizes frictional losses.

**APPLICATION:** Recommended as cylinder lubricants for steam engines handling superheated steam. It is recommended where Heavy loads, Slow speeds or High temperatures demands high viscosity lubricants in bearings and enclosed gear sets. It is suitable for worm gear boxes.



Recommended as lubricants for steam engines and cylinder.

**PERFORMANCE LEVEL:** Proprietary product

### TYPICAL PROPERTIES:

TYPICAL PROPERTIES	EASTTO CYLINDER OILS		
	680	1000	1500
Kinematic Viscosity @ 40°C, cst	680	1000	1500
Viscosity Index	85	80	80
Flash Point (COC) °C	280	280	280
Pour Point °C	-3	-3	-3

**PACKING:** 210 Litres Drum

**Date of Issue :** 13.09.2014

**Date of revision:** 08.08.2016

**1<sup>st</sup> Revision:** 29.05.2019 (CK)

**PDS No.** 20600 - 20602





**Eastern Petroleum Pvt. Ltd.**

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,  
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990

Email: [office@easternpetroleum.in](mailto:office@easternpetroleum.in), Web: [www.easternpetroleum.in](http://www.easternpetroleum.in)

CIN NO:U24100MH1964PTC012931

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.**  
Specification variation in these characteristics may occur.

