

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg, (Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,
Email: office@easternpetroleum.in, Web:www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

PRODUCT DATA SHEET

PRODUCT:	EASTTO MAX A (PARAFFINIC RICH LOW AROMATIC SOLVENT)
INTRODUCTION:	EASTTO MAX A is chemically processed specially formulated solvent, free from aromatics and unsaturated hydrocarbons. It is odourless, clear and colourless liquid.
APPLICATION:	It is widely used in manufacture of Polish, Metal degreasing products, Specialty lubricants, Agrochemicals, Paints, Printing inks, Rust preventives, Aerosols, Ultra sonic cleaning agent, Thinner, Lube oil additives, Pesticides, Insecticide, Specialty chemicals, Fuel additive, Drilling fluid, Mosquito repellents and a solvent for industrial application.







Metal Degreasing Products, Agrochemicals, Rust preventive products etc.

TYPICAL PROPERTIES:

SR. NO.	CHARACTERISTICS	EASTTO MAX- A
1.	Appearance	Bright & Clear Liquid
2.	Odour	Odourless
3.	Specific Gravity @ 30 ℃	0.77
4.	Acidity	Nil
5.	Flash Point °C	65
6.	Kinematic Viscosity @ 40 °C, cst	1.7
7.	Aromatics	Less than 1%
8.	Boiling Range – IBP °C	180
9.	FBP °C	240

PACKING: 20 Litres M. S. Drums / Tanker Load.

Date of Issue: 20.12.2014

Date of Revision: 06.03.2017

PDS No. 11.10.01

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.

