



Eastern Petroleum Private Limited

an ISO 9001-2008 certified company

Eastto Metalhone TX

INTRODUCTION: EASTTO METALHONE TX is a very light coloured and low viscosity oils with good lubricity characteristics for honing operations of all ferrous and non-ferrous metals with good surface finish. This oil has excellent chip flushing, good heat carrying capacity and better visibility of work piece and tool, and provides long life to the honing stone.

APPLICATION: EASTTO METALHONE TX is suitable for machining of operations, like turning, drilling, tapping, honing, broaching, boring etc. of all ferrous and non-ferrous metals and their alloys where non-staining type light coloured and low viscosity oil is useful very good surface finish.

PERFORMANCE LEVEL : METALHONE TX is a proprietary product.

TYPICAL PROPERTIES

CHARACTERISTICS	EASTTO METALHONE TX
Kinematic Viscosity at 40°C, cSt	4.0 - 6.0
Flash Point, COC, °C, Min.	130
Copper Strip Corrosion Test at 100°C for 3 Hrs.	1
Pour Point, °C, Max.	-9

PACKING: 210 Litres Drums



Eastto
Metalhone TX



Eastern Petroleum Private Limited

Regd. Off.:
Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.
Tel.: +91 - 22 - 4232 4121, +91 - 22 - 2529 9990
Email: office@easternpetroleum.in, office@eastto.in,
Web: www.easternpetroleum.in, www.eastto.in

