

PRODUCT DATA SHEET

PRODUCT: EASTTO TRANSFORMER OIL 335

INTRODUCTION: EASTTO TRANSFORMER OIL 335 having excellent insulating properties, good oxidation stability, low volatility and resistance to sludge formation. **EASTTO TRANSFORMER OIL 335** is free from Acid, Alkali and Corrosive sulphur and excellent demulsibility characteristic.

APPLICATION: Recommended for use in Electrical Capacitors, High voltage switches Circuit Breakers, Transformers, Electrical parts, Fluorescent lamp ballasts.



Recommended for use in Capacitors, Circuit Breakers and Transformers.

PERFORMANCE LEVEL: Meets IS 335-1993 (Reaffirmed 2005) specification.

TYPICAL PROPERTIES:

CHARACTERISTICS	EASTTO TRANSFORMER OIL 335
Density at 30 °C	0.890
Flash Point, °C	140
Pour Point °C.	- 6
Kinematic Viscosity at 27°C, cst	27
Breakdown Voltage, new unfiltered / after filtration	30 / 60
Corrosive Sulphur	Non-corrosive
Oxidation Stability at 100°C, 164 Hrs.	
a) Total Acidity	a) 0.4
b) Sludge	b) 0.1
Water Content, ppm	50
Presence of Oxidation Inhibitor	Nil

PACKING: 210 Litres Drums

Date of issue: 10.11.2014

Date of revision: 11.08.2016

1st Revision: 29.05.2019 (CK)

PDS No. 30700

These Characteristics are typical of current production while future production will confirm to **EASTERN PETROLEUM PVT. LTD.** Specification variation in these characteristics may occur.





Eastern Petroleum Pvt. Ltd.

an ISO 9001-2008 certified company

Regd. Off.: Unit No. 1, Riddhi Siddhi, Corporate Park, V. N. Purav Marg,
(Sion Trombay Road), Chembur, Mumbai - 400 071. MH, India.

Tel.: +91 - 22 - 4232 4121, 2529 9990,

Email: office@easternpetroleum.in, Web: www.easternpetroleum.in

CIN NO:U24100MH1964PTC012931

